



Dressing Spindles

ドレッシングスピンドル



customized service
カスタマイズサービス

DRESSING SPINDLES



型番 Description	SYD-58-25K -0.76kW-PM	SYD-72 -16K-0.6kW	SYD-72-16K -0.7kW-PM	SYD-80 -16K-1.6kW	SYD-80-16K -1.6kW-PM	SYD-80-16K -4.4kW-PM
主軸外径 Housing Diameter (mm)	φ58	φ72	φ72	φ80	φ80	φ80
回転数 Operating Speed (RPM)	25,000	16,000	16,000	16,000	16,000	16,000
基準回転速度 Nominal Speed (RPM)	25,000	16,000	16,000	11,000	11,000	11,000
出力 Power S1/S6 (kW)	0.58/0.76	0.5/0.6	0.5/0.7	1.3/1.6	1.3/1.6	3.7/4.4
電圧 Motor Voltage (V)	220V	220V	220V	220V	220V	220V
モータータイプ Motor Type	Synchronous	Asynchronous	Synchronous	Asynchronous	Synchronous	Synchronous
トルク Torque S1/S6 (Nm)	0.22/0.29	0.3/0.36	0.31/0.4	1.1/1.4	1.1/1.4	3.2/3.8
ベアリング潤滑方式 Bearing Lubrication	Grease	Grease	Grease	Grease	Grease	Grease
軸端形状 Tool Interface	φ20*10	φ40*10	φ40*10	φ40*10	φ40*10	φ40*10
冷却タイプ Motor Cooling	Air	Water	Air	Water	Air	Water
スラスト剛性値 Axial Rigidity (N/um)	34	68	68	90	90	90
ラジアル剛性値 Radial Rigidity (N/um)	42	53	53	75	75	75